CAMBRIDGE INTERNATIONAL EXAMINATIONS

Cambridge Ordinary Level

MARK SCHEME for the October/November 2014 series

5054 PHYSICS

5054/21 Paper 2 (Theory), maximum raw mark 75

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2014 series for most Cambridge IGCSE®, Cambridge International A and AS Level components and some Cambridge O Level components.

Section A

1	(a)	(i)	(a =) (v – u) / t **or** $\Delta v / t$ **or** (55–40) / 2 **or** equivalent values from graph	C1	
			7.5 m / s^2	A1	
		(ii)	(F =) ma **or** 180 × 7.5	C1	
			1300 / 1350 / 1400 N	A1	
	(b)	(i)	(acceleration) decreases (to zero)	B1	
		(ii)	air resistance / friction / drag mentioned	B1	
			air resistance / friction / drag increases (with speed) **or** resultant force decreases (with speed)	B1	
			(finally) (air) resistance = driving force **or** resultant is zero	B1	**[8]**
2	(a)	(i)	$F_1 \times d_1 = F_2 \times d_2$ **or** (0.39 × 0.40) / 0.30	C1	
			0.52 N	A1	
		(ii)	0.052 kg **or** 52 g	B1	
	(b)		(ρ =) m / V **or** 52 / 60 **or** 0.052 / 0.000 060 **or** 0.052 / 60	B1	
			870 / 867 / 866.7 kg / m^3 **or** 0.87 g / cm^3 **or** 8.7 × 10^{-4} kg / cm^3 etc.	B1	**[5]**
3	(a)		(atoms / molecules / particles) move (about) / collide / hit	B1	
			(atoms / molecules / particles) collide / hit the walls / surface (of the cylinder)	M1	
			force on walls (causes pressure)	A1	
	(b)		atoms / molecules / particles closer / more compact / more molecules per unit volume / less space to move	B1	
			more collisions with the wall / surface (of chamber) **not** if speed / KE changes	B1	**[5]**
4	(a)		any **two** from: transmission of energy without net movement of medium through vibration of particles	B2	
	(b)	(i)	number of (complete) waves / cycles / oscillations per unit time / second	B1	
		(ii)	distance between (neighbouring) waves	C1	
			distance between (neighbouring) wavefronts / points of same phase **or** crest to crest / tough to trough distance	A1	
	(c)		three reflected wavefronts roughly correct direction	M1	
			wavelengths equal to each other and incident wavelength by eye	A1	
			reflected wavefronts joined to incident wavefronts	B1	**[8]**

5	**(a)**	longitudinal / pressure / sound (wave) **or** compressions **and** rarefactions (frequency) greater than 15 – 25 kHz / above limits of audibility	B…	
	(b)	(x =) vt / 2 **or** 340 × 0.030 / 2 **or** 340 × 0.015 **or** 10.2 5.1 m	C1 A1	**[4]**
6	**(a)**	**electrons** repelled by cloud (leaving ground positive) **not** positive charge / protons move like charges repel **or** electrons negative	B1 B1	
	(b)	(region) where (electric) charge experiences a force	B1	
	(c)	(I =) Q / t **or** 180 / 0.0015 1.2×10^5 A	C1 A1	**[5]**
7	**(a)**	wire cuts field lines current / e.m.f. / voltage **induced**	B1 B1	
	(b)	larger deflection **and** to the left / opposite direction	B1	
	(c)	no deflection / current	B1	**[4]**
8	**(a)**	neutrons and protons together and alone in the middle 5 protons 7 neutrons (if protons and neutrons unlabelled 1/2) 5 electrons **and** electrons surrounding nucleus	B1 B1 B1 B1	
	(b)	**(i)** 6	B1	
		(ii) 12	B1	**[6]**

[Total: 45]

Section B

9 (a) any **two** from:
biomass / wood; geothermal power; solar power; tidal power; wave power; wind power — B2 **[2]**

(b) (i) 1. $2.1(4) \times 10^{17}$ J (**allow** $2.1(5) \times 10^{17}$ J if candidate uses 365.24 / 5) — B1
2. any **one** from: not enough water (to maintain maximum flow); rainfall varies (during the year); periods of low demand — B1

(ii) 1. (GPE =) mgh **or** $1.6 \times 10^{10} \times 10 \times 170$ — C1
$2.7(2) \times 10^{13}$ J — A1
2. $2.7(2) \times 10^{13} / 3600$ **or** $6.8 \times 10^{9} \times 3600$ **or** $6.8 \times 10^{9} / 7.5(55) \times 10^{9}$ **or** $2.4(48) \times 10^{13} / 2.7(2) \times 10^{13}$ — C1
0.90 **or** 90% — A1
3. any **two** from:
friction (of water) with pipe / turbine /; viscosity of water; friction at bearings; resistance / heat in the wires; KE of water leaving turbine — B2 **[8]**

(c) (i) less energy lost / wasted **or** more efficient — B1
(for a given power) a high voltage results in a small(er) current — B1
less heat generated in wires **or** I^2R **or** less resistive losses (**not** if <u>changed</u> resistance mentioned) — B1

(ii) transformer — B1

(iii) transformers only work with an a.c. supply — B1 **[5]**

[Total: 15]

10 (a) (i) **heated / hot water** expands **or** density of **heated / hot water** decreases — B1
(heated / hot water) rises — B1
convection (current) / circulation set up **or** (heated / hot water) rises **and** cold water sinks — B1

(ii) convection transfers heat upwards **or** less dense / heated / hot water (already) at top — B1 **[4]**

(b) (i) (Q =) VIt **or** $230 \times 9.6 \times 3.5$ **or** $230 \times 9.6 \times 3.5 \times 60$ **or** 7728 — C1
$4.6(368) \times 10^{5}$ J — A1

(ii) (ΔT =) Q / mc **or** $4.6(3680) \times 10^{5} / 1.6 \times 4200$ — C1
69 (°C) — C1
91 °C — A1

(iii) evaporation **or** thermal energy / heat in **plastic casing / element / surroundings** (i.e. air or environment) — B1 **[6]**

(c) (i) poor conductor (heat or electricity) **or** less heat lost / cooler to touch **or** less risk of shock B1

(ii) poor emitter **and** less heat lost / of radiation / IR (**not** poor absorber) B1

(d) (i) **temperature** where liquid and vapour/gas coexist **or** where liquid (**not** substance) boils
(at atmospheric pressure)(**allow** becomes vapour/gas) B1

(ii) (work done) against / overcoming forces between molecules **or** molecules gain P.E. (**ignore** K.E. increases) B1
changes to P.E. / molecules separate B1 **[3]**

[Total: 15]

11 (a) (i) energy to drive charge around a circuit **or** terminal p.d. on open circuit B1
energy to drive **unit** charge around a circuit **or** energy / charge B1

(ii) lasts longer **or** lower internal resistance **or** can replace a cell without switching off **or** continues to work if one cell is flat **ignore** more current (**not** greater e.m.f. / voltage) B1 **[3]**

(b) (i) 4.0 Ω B1

(ii) $(1/R_{tot} =) 1/R_1 + 1/R_2$ **or** $1/3 + 1/X$ **or** product / sum **or** $(3 \times X)/(3 + X)$ **or** $\frac{1}{X} = \frac{1}{2} - \frac{1}{3}$ C1
6.0 Ω A1 **[3]**

(c) (i) $(I =) V/R$ **or** 2.0 / 4.0 C1
0.50 A A1

(ii) (from) 0 **and** (to) 0.50 to 5.0 A B1 **[3]**

(d) $I_2 = I_3 + I_X$ B1 **[1]**

(e) (i) 1.0 V B1

(ii) 1.0 V B1 **[2]**

(f) (i) temperature decreases B1
resistance decreases B1

(ii) greater than 0.75 A (e.c.f. resistance increases in **(f)(i)**) B1 **[3]**

[Total: 15]